



**Motorlåser**

	Abloy	Abloy	Abloy	Abloy	Abloy	Abloy	Abloy	Abloy	Assa	Assa	Assa	Assa	Assa	Assa
<b>Låstyppe</b>	EL572	EL573	EL648	EL574	EL575	EL874	EL875	EL654 Hi-O	840C Hi-O	841C	841C35	850C	851C	851C35
<b>Forsikringsklasse</b>	2A*	2A*	2A*	2A*	2A*	2B*	2B*	3	4	4	4	5	5	5
<b>Styreenhet</b>			EA460	EA452	EA452	EA453	EA453	DAC564III	DAC564III	DAC564III	DAC564III	DAC564III	DAC564III	DAC564III
<b>Nødutstyr</b>	5931 m/5542M 5934 m/5572M	5931 m/5542M 5934 m/5572M	EA200	5931 m/5542M 5934 m/5572M	5931 m/5542M 5934 m/5572M	Assa 179C	Assa 179D	EA200	5931 m/5542 5934 m/5572	5931 m/5542 5934 m/5572	NB851	5931 m/5542 5934 m/5572	5931 m/5542 5934 m/5572	NB851
<b>Kabel</b>	EA221	EA221	EA224	EA224	EA224	EA224	EA224	EA226*	EA226*	EA226*	EA226*	EA226*	EA226*	EA226*
<b>Kabelsignal</b>	Analog	Analog	Analog	Analog	Analog	Analog	Analog	Hi-O Kryptert	Hi-O Kryptert	Hi-O Kryptert	Hi-O Kryptert	Hi-O Kryptert	Hi-O Kryptert	Hi-O Kryptert
<b>Karm.over</b>	EA281	EA281	EA281	EA281	EA281	EA281	EA281	EA281	EA281	EA281	EA281	EA281	EA281	EA281
<b>Sikkerhetsskilt</b>			SK5974					SK5974			SK4559			SK4559
<b>Anb. Syl-sett</b>	xx85C	xx85C	xx55C	xx85C	xx85C	xx85	xx85	xx55C	xx85C	xx85C	xx55C	xx86C	xx86C	xx55C
<b>Sluttstykke</b>	EA342	EA342	EA300	EA342	EA342	EA342	EA342	EA300	1487-2	1487-2	1487-8	1487-2	1487-2	1487-8
<b>Slagretning</b>	R eller L			R eller L		R eller L	R eller L		R / L vendbar			R / L vendbar		
<b>Backset</b>	50mm	50mm	25/35mm	50mm	50mm	50mm	50mm	25/35mm	50/70mm	50/70mm	35mm	50mm	50mm	35mm

**Tekniske data.**

<b>Driftsspennning</b>	12-24VDC	12-24VDC	12-24VDC 12-18VAC	12-24VDC 12-18VAC	12-24VDC 12-18VAC	12-24VDC 12-18VAC	12-24VDC 12-18VAC	17-24VAC/DC 12VDC	17-24VAC/DC 12VDC	17-24VAC/DC 12VDC	17-24VAC/DC 12VDC	17-24VAC/DC 12VDC	17-24VAC/DC 12VDC	17-24VAC/DC 12VDC
<b>Variasjon Volt</b>	±10/+15%	±10/+15%	±10/+15%	±10/+15%	±10/+15%	±10/+15%	±10/+15%	±15%	±15%	±15%	±15%	±15%	±15%	±15%
<b>Stab. VDC</b>	JA	JA	JA	JA	JA	JA	JA	JA	JA	JA	JA	JA	JA	JA
<b>Strømforbruk 24V</b>	mA	mA	mA	mA	mA	mA	mA	mA	mA	mA	mA	mA	mA	mA
<b>Hvile/Drift/Maks</b>	25-100-250	25-100-250	70-150-700	35-100-150	35-100-150	35-100-150	35-100-150	70-150-750	50---445	50---445	50---445	50---445	50---445	50---445
<b>Åpne hastighet</b>	0,7 sek.	0,7 sek.	0,8 sek.	0,7 sek.	0,7 sek.	0,7 sek.	0,7 sek.	0,8 sek.	0,2 sek.	0,2 sek.	0,2 sek.	0,2 sek.	0,2 sek.	0,2 sek.
<b>Hakereile fremspring</b>	20mm	20mm	22mm	20mm	20mm	20mm	20mm	22mm	22mm	22mm	22mm	22mm	22mm	22mm
<b>Godkjent for</b>														

ASSA 840C og 841C kan leveres i 70mm backset.

\* Alle motorlåser i FG klasse 2A og 2B er godkjent i dagens klasse 3 frem til 31.12.2019.